

# MES 12x15x10



- Mobile Environmental Solutions Inflatable Workstations are built to the NFPA's CH 33 14.4 standard of construction and design requirements.
- Exhaust filters exceed the EPA's 6HHHHHH rule of 98% capture efficiency.
- Mobile Environmental Solutions Inflatable Workstations ventilation air flow exceeds OSHA's 1910.107 requirement of 100 linear feet per minute.
- Mobile Environmental Solutions Inflatable workstations are designed to have a lower flammable limit of less than 10% with clean filters. This 12x15x10 has an estimated 68.2 air exchanges per hour or 0.9 per minute.

## **DIMENSIONS:**

- Exterior Length 12 Feet or 3.65 Meters
- Exterior Width 15 Feet or 4.57 Meters
- Exterior Height from center 10 Feet or 3 Meters
- Total footprint 180 SQ FT or 16.68 Meters
- Interior Length 10.5 Feet or 3.5 Meters
- Interior Width 12 Feet or 3.65 Meters
- Interior Side Height 6.5 Feet or 2 Meters
- Interior Center Height 8.5 Feet or 2.6 Meters
- Interior Door Clearance Height 6.9 Feet or 2.74 Meters
- Inflatable Weight 170 LBS or 77.11 KG

## **WARRANTY:**

All Mobile Environmental Solutions Inflatable Workstations are made in the United States. New units come with a standard 1-year warranty towards manufactures defects from the date of purchase. Air Movers come with a 2-year warranty when the owner registers them at the time of purchase.

## **INCLUDED EQUIPMENT:**

- 2 Replaceable Exhaust Filters that exceed EPA's 6HHHHHH Rule.
- 8 Replaceable Inlet Filters
- 4 Lower Anchoring support D-Rings
- 4 Upper Support D-Rings
- 2 Roof Support D-Rings
- 2 Replaceable Side Windows
- 4 Tie Down Straps
- 4 Sandbags
- 1 Replaceable Floor
- 1 Replaceable Front Door
- 1 Replaceable Back Door
- 4 Emergency Exits
- 1 Storage Bag
- 1 Repair Kit
- 1 Certified ETL and CE approved 1.5HP 115V 60HZ and 230V 60HZ air movers.
- 2 Air Hose access slots
- 1 Operational Manual

