MES 30x17x12



- · Mobile Environmental Solutions Inflatable Workstations are built to the NFPA's CH 33 14.4 standard of construction and design requirements.
- · Exhaust filters exceed the EPA's 6HHHHHH rule of 98% capture efficiency.
- · Mobile Environmental Solutions Inflatable Workstations ventilation air flow exceeds OSHA's 1910.107 requirement of 100 linear feet per minute.
- · Mobile Environmental Solutions Inflatable workstations are designed to have a lower flammable limit of less than 10% with clean filters. This 30x17x12 has an estimated 56.5 air exchanges per hour or 1.1 per minute.

DIMENSIONS:

- -Exterior Length 29.83 Feet or 9 Meters
- -Exterior Width 17 Feet or 5.18 Meters
- -Exterior Height from center 12 Feet or 3.65 Meters
- -Total footprint 507.11 SQ FT or 46.62 Meters
- -Interior Length 22.66 Feet or 6.9 Meters
- -Interior Width 14 Feet or 4.26 Meters
- -Interior Side Height 8.23 Feet or 2.5 Meters
- -Interior Center Height 10.5 Feet or 3.2 Meters
- -Interior Door Clearance Height 8.6 Feet or 2.62 Meters
- -Inflatable Weight 414 LBS or 187.787 KG

WARRANTY:

All Mobile Environmental Solutions Inflatable Workstations are made in the United States. New units come with a standard 1-year warranty towards manufactures defects from the date of purchase. Air Movers come with a 2-year warranty when the owner registers them at the time of purchase.



INCLUDED EQUIPMENT:

- -3 Replaceable Exhaust Filters that exceed EPA's 6HHHHHH Rule.
- -20 Replaceable Inlet Filters
- -6 Lower Anchoring support D-Rings
- -12 Upper Support D-Rings
- -6 Roof Support D-Rings
- -10 Replaceable Side Windows
- -12 Tie Down Straps
- -12 Sandbags
- -1 Replaceable Floor
- -1 Replaceable Front Door
- -1 Replaceable Back Door
- -4 Emergency Exits
- -1 Storage Bag
- -1 Repair Kit
- -3 Certified ETL and CE approved 1.5HP 115V 60HZ and 230V 60HZ air movers.
- -2 Air Hose access slots
- -1 Operational Manuel