## MES 30x17x14



- · Mobile Environmental Solutions Inflatable Workstations are built to the NFPA's CH 33 14.4 standard of construction and design requirements.
- Exhaust filters exceed the EPA's 6HHHHHH rule of 98% capture efficiency.
- · Mobile Environmental Solutions Inflatable Workstations ventilation air flow exceeds OSHA's 1910.107 requirement of 100 linear feet per minute.
- · Mobile Environmental Solutions Inflatable workstations are designed to have a lower flammable limit of less than 10% with clean filters. This 30x17x14 has an estimated 31.3 air exchanges per hour or 1.9 per minute.

## DIMENSIONS:

- -Exterior Length 29.8 Feet or 9 Meters
- -Exterior Width 17 Feet or 5.18 Meters
- -Exterior Height from center 14 Feet or 4.26 Meters
- -Total footprint 507.11 SQ FT or 46.62 Meters
- -Interior Length 28.3 Feet or 8.63 Meters
- -Interior Width 114 Feet or 4.26 Meters
- -Interior Side Height 10.26 Feet or 3.12 Meters
- -Interior Center Height 12.5 Feet or 3.81 Meters
- -Interior Door Clearance Height 10.7 Feet or 3.26 Meters
- -Inflatable Weight 443 LBS or 201 KG

## WARRANTY:

All Mobile Environmental Solutions Inflatable Workstations are made in the United States. New units come with a standard 1-year warranty towards manufactures defects from the date of purchase. Air Movers come with a 2-year warranty when the owner registers them at the time of purchase.



## INCLUDED EQUIPMENT:

- -3 Replaceable Exhaust Filters that exceed EPA's 6HHHHHH Rule.
- -18 Replaceable Inlet Filters
- -6 Lower Anchoring support D-Rings
- -12 Upper Support D-Rings
- -6 Roof Support D-Rings
- -10 Replaceable Side Windows
- -12 Tie Down Straps
- -12 Sandbags
- -1 Replaceable Floor
- -1 Replaceable Front Door
- -1 Replaceable Back Door
- -4 Emergency Exits
- -1 Storage Bag
- -1 Repair Kit
- -3 Certified ETL and CE approved 1.5HP 115V 60HZ and 230V 60HZ air movers.
- -2 Air Hose access slots
- -1 Operational Manuel