



PROFESSIONAL LIFTING EQUIPMENT

# WHEN SAFETY DEPENDS ON PERFORMANCE!


**78090A**



## 3,600 Lbs. Capacity Car Dolly

### INTENDED USE

*For easy movement of vehicles that have been rendered inoperable due to engine/ transaxle removal or other mechanical problems. Frees up lifts and floor jacks for other work to be performed. Used in automobile repair, collision repair, and vehicle inspection applications.*



- Supports a vehicle with or without tires.
- Allows FWD vehicle to be easily moved in the service bay when drive train has been removed.
- Universal design fits any car without the need for additional vehicle adapters.
- Quick and independent width and height adjustments. Fully adjustable outriggers to fit any vehicle frame width. Threaded lift saddles with rubber pads are independently adjustable and provide maximum frame protection.
- Does not require installation to the subframe or engine/transaxle cradle mounting holes.
- Can be used in pairs for maximum maneuverability in tight places.
- Four 6" diameter ball bearing mounted swivel caster wheels rated at 900 pounds capacity each.
- Two of the four 6" wheels have wheel locks to prevent dolly from moving.

MODEL NUMBER	CAPACITY	HEIGHT ADJUSTMENT	WIDTH	LENGTH ADJUSTMENT	SHIPPING WEIGHT
<b>78090A</b>	<b>3,600 lbs.</b>	12.75" to 15.75"	17"	30" to 60"	65 lbs.