

# 13120 55 TON ALUMINUM JACK

## **55 TON ALUMINUM JACK**

- Lightweight aluminum for easily handling and placing under the vehicle
- Includes "Shut-Off Valve" which allows the pump to be removed while the ram is extended
- Aluminum base plate included on 55 Ton models
- 55 ton capacity
- 6" (15 cm) stroke
- 18.25" (46 cm) max. height
- Weight: 29 lbs (13.2 kg)





#### THE INDUSTRY'S TOP JACK JUST GOT BETTER

As a part of AME's continuous improvement culture, we've taken a best selling product and made it even more user friendly.

#### **ORIGINAL**



### **Durability Improvements:**

- Tighter fit between the piston and wear bands implemented to reduce deflection during side load conditions.
- Hard Coating added to the piston bearing surfaces to reduce the amount of scoring if a cylinder strike still happens during side loaded conditions.
- Tighter interference fit between the gland and cylinder walls combines with improved wear band fit to reduce side-load deflection even more.
- Reminder: while this product improvement reduces incidence of side load it is still recommended that jacks are used for lifting only. It is best practice to use jack stands or cribbing to support the load.

#### **UPDATED**



www.ameintl.net

2347 Circuit Way Brooksville Fl, 34604 352-799-1111 - sales@ameintl.net





