



AC Hydraulic^{A/S}
NO COMPROMISE

By



65-1H

AIR HYDRAULIC JACK

2-Stage Air Hydraulic Jack

- Air hydraulic jack for heavy duty applications with high clearance
- Minimum height of 16.65 in
- Maximum height of 28.50 in and with extensions up to 40.31 in
- Designed for heavy-duty, intensive commercial use
- Hard chromium plated piston rod for long life
- Built-in safety overload valve
- Hand-operated dead-man's control for optimum safety whilst lifting and lowering
- 65-1HTH model with telescopic handle increasing the reach under the vehicle to 2337 mm ensuring safe and easy operation
- With 2 extensions (3.94/7.87 in)

Technical data	65-1H	
Capacity	143000 lb	65 t
Min. height	16.23 in	425 mm
Max. height	28.54 in	725 mm
Frame length	38.58 in	980 mm
Handle length	53.35 in	1355 mm
Width	11.81 in	300 mm
Width (with wheels)	14.96 in	380 mm
Air supply	9 - 12 bar	9 - 12 bar
Air consumption	350 l/min	350 l/min
Weight	304 lb	138 kg



2347 Circuit Way
Brooksville, FL 34604
352.799.1111 - sales@ameintl.net



www.ameintl.net