


HYDRAULIC RAMS - Single Acting Cylinders

model(s) 10301 | 10302 | 10303 | 10304 | 10305 | 10306 | 10310










Removable rubber boots protect collar threads during transport and storage.



Fitted with 3/8 in. NPTF female half couplers.



- Rugged, high quality rams/cylinders designed for use in lifting and pushing.
- Aluminum bronze bearings reduce wear caused by off-center loads.
- Solid steel cylinder design increases durability.
- Chrome plated piston resistant to wear and corrosion.



It is recommended to only use **80%** of the stroke of cylinders & rams to maximize the products performance, safety, and lifespan.

















| SPECIFICATIONS: | 10301 | 10302 | 10303 | 10304 | 10305 | 10306 | 10310 |
|----------------------|--------------------|--------------------|--------------------|---------------------|---------------------|--------------------|-----------------------|
| Ram Tonnage | 10 Tons | 10 Tons | 10 Tons | 10 Tons | 10 Tons | 30 Tons | 25 Tons |
| Stroke (B) | 2.13 in. 54 mm | 4.13 in. 105 mm | 6.13 in. 156 mm | 8 in. 203 mm | 10.13 in. 257 mm | 2.44 in. 62 mm | 6.25 in. 158.8 mm |
| Retracted Height (A) | 4.75 in. 121 mm | 6.75 in. 72 mm | 9.75 in. 248 mm | 11.75 in. 299 mm | 13.75 in. 350 mm | 4.63 in. 118 mm | 10.75 in. 431.8 mm |
| Max Pressure | 10,000 PSI | 10,000 PSI | 10,000 PSI | 10,000 PSI | 10,000 PSI | 10,000 PSI | 10,000 PSI |
| Weight | 6 lbs. 3 kg | 8 lbs. 4 kg | 11 lbs. 5 kg | 12 lbs. 5 kg | 14 lbs. 6 kg | 15 lbs. 7 kg | 21.7 lbs. 9.8 kg |
| Warranty | 3-Year Warranty | 3-Year Warranty | 3-Year Warranty | 3-Year Warranty | 3-Year Warranty | 3-Year Warranty | 3-Year Warranty |
| UPC | 816904021627 | 816904021634 | 816904021641 | 816904021658 | 816904021665 | 816904021672 | 816904025403 |

