91003.11.2022 .A

The **MAMMUT RANGE OF JACKS** offers service professionals a solution that is safe and easy to use, for all those operations to lift earthmoving, construction, quarry, and mining machinery, where maintenance requires professional skills and expertise. All models are air/hydraulic operated and equipped with a dual descent valve for greater control when bearing weight and automatic piston return; they can also be fitted with a manual emergency pump (on request).

## Specifications

MAMMUT		A	57.9 in   1473 mm
		B	21.6 in   550 mm
		с	43.4 in   1102 mm
	A	D	33 in   839 mm
		E	24.2 in   617 mm
c	B	F	16.4 in   419 mm

## Accessories

-		(Inter-up)	Model	Description	Specs
		91033	Extension Holder R	NA	
	1 - N	-	91032	Extension Holder L	NA
91033	91032	91038	91038	Extension	A: 3.125 in B: 1.5 in. C: 0.75 in. A: 80mm B: 35mm C: 20mm
		91028	91026	Extension	A: 6 in B: 1.5 in C: 0.75 in A: 150mm B: 35mm C: 20mm
			91027	Extension	A: 9.875 in B: 1.5 in C: 0.75 in A: 250mm B: 35mm C: 20mm
91026	91026 91027		91028	Extension	A: 11.875 in B: 1.5 in C: 0.75 in A: 300mm B: 35mm C: 20mm
91042		<sup>₩<sup>@</sup>C</sup>	91042	Tilting Plate	A: 1.875 in B: 1.5 in A: 46mm B: 35mm
	ø A	91022	Safety Lock Holder	Safety Lock Holder Vertical Safety Lock Holder Eyebolt Extension (4) Safety Block - (H) 4 in - (W) 6 in Safety Block - (H) 2 in - (W) 6 in	

NOTE: ESCO reserves the right to change, alter, or modify product(s) without notice. This includes but is not limited to product: color, design, parts, accessories, etc.

## sales@esco.net WWW.ESCO.NET 1.800.352.9852

**FSCO** 

You Tube

