

9,000 LB. CAPACITY FEATURES



Direct Drive Hydraulic Cylinders (9KMSC)

Overhead Shut-off Bar w/Limit Switch (9KMSC)

Chain Over Roller Hydraulic Cylinders (9KMSF)

Single Button Operation / Single Lever Lowering

Serviceable Arm Restraint Locks

Thread-up Lifting Pads

Carriage Limit Switch

3-Stage Front Arms

Single-Point Lock Release

European Style Carriages

4" Truck Adapters

Rubber Door Guards

Steel Toe-guards

Steel Hydraulic Oil Reservoir

2 Year Electric/Hydraulic Warranty / 5 Year Structural Warranty

Lifetime Warranty on Nylon Slide Blocks

Durable Textured Powder-coated Finish

CLEARFLOOR SPECIFICATIONS

Power Unit: 220V

Lifting Speed: 50-60 sec

Width Between Columns: 111-1/2"

Drive Thru Clearance: 100-3/4"

Min/Max Pad Height: 3-3/4" - 82- 1/4"

Baseplate to Baseplate Width: 134-5/8"

Column Height: 140-3/4" *CYLINDERS WILL EXTEND 7-7/8" THROUGH THE TOP PLATES WHEN LIFT IS RAISED TO MAX HEIGHT.



FLOORPLATE SPECIFICATIONS

Power Unit: 220V

Lifting Speed: 50-60 sec

Width Between Columns: 111-1/2"

Drive Thru Clearance: 100-3/4"

Min/Max Pad Height: 3-3/4" - 80-1/4"

Baseplate to Baseplate Width: 134-1/4"

Column Height: 112"

* CARRIAGE LOCK LADDER WILL EXTEND 10" ABOVE TOP OF COLUMN WHEN RAISED TO MAX HEIGHT.

TITANLIFTS.COM
888-908-4826