

25", 37", 43" Wide Belt Sanders



The Gold Standard Since 1921.®

POWERMATIC®

25", 37", 43" Wide Belt Sanders

FEATURES

Centralized controls allow you to access all the needed buttons right on one simple panel for more convenience

The variable speed feed belt allows you to accurately dial in the exact feed speed to best suit your project and work environment

Digital readout will show you the exact thickness of the finished piece or will allow the user to preset exactly what thickness they would prefer for the finished piece

The disc brake slows the machine quickly and kicks in to quickly stop the machine in an emergency

The air-eye system controls the oscillation for the sanding belts. This prevents the belt from running off the end of the drums as well as uses the sanding surface more uniformly without leaving sanding lines on the work piece

The auto thicknesser will capture the workpiece to give the user an exact thickness

The three motor system allows for maximum horsepower to feeds the drive drums, a second smaller motor to directly power the VS feed belt and a third smaller motor to easily and automatically power the feed table up and down to the desired thickness

Model Number	WB-25	WB-37	WB-43
Stock Number	1790825	1790837	1790843
Working Width	25	37	43
Max Thickness	6	6	6
Minimum Board Length	12	12	12
Main Drive Motor	15HP	20HP	25HP (ALL 3Ph, 230V / 460V*, Prewired 230V)*Additional parts required.
Power Feed Motor	1HP	1HP	1HP (All 3Ph)
Table Hoist Motor	1/4HP	1/4HP	1/4HP (All 3Ph)
Sanding Belt Size (in.)	25 x 75	37 x 75	43 x 75
Dust Ports (in.)	2 - 5	2 - 5	2 - 5
Gross Weight	1760	2090	2530
NET Weight	1650	1970	2400