

E2.1F3H1



Hydraulic Power Units

SKU# 5585285

3.6 Gal Reservoir, 2,650 PRV, 2.5 HP Motor, 208-230V / 50-60 Hz / 1 Ph, UL/ETL Listed

Questions? Contact BendPak's Sales Team

sales@bendpak.com | 1-800-253-2363

Monday - Friday, 7AM to 4:30PM PST

Need a Lift? Ranger Has a Power Unit for the Job

This [hydraulic power unit](#) exists solely to get your vehicle lifted fast. The rugged 2.5 HP motor accompanies an increased 3.6-gallon tank, all of which provide an extra boost of power. Low-rise car lifts will zip up to their max extension at incredible speeds; likewise, this unit is made to handle full-size two-post and four-post lifts without breaking a sweat. As always, Ranger Products assures the highest quality of construction and most advanced safety features.

Features

- High mechanical and volumetric efficiency
- End head prepared for lift-hold-lower applications using our manual lowering valve or solenoid cartridge valves.
- Totally enclosed motors are suitable for use in humid environments or dusty, contaminated atmospheres. UL Recognized AC electric motors feature heavy gauge steel frame and high-quality ball bearings.
- Torque load remains constant throughout operation.
- Heavy-duty start switches with a high IP-protection class and silver-plated contacts for a long service life.
- Cartridge-style relief valves meet tough demands for dependability and life expectancy.
- Minimum recommended temperature is -25°C (-13°F).
- Maximum recommended temperature is +80°C (+175°F).
- 12-months warranty

Specifications

SKU#	Model	Reservoir	PRV	HP	Cert
5585280	F2.1F3H1	3.6 gal	2,850	2.5	UL/ETL
5585285	E2.1F3H1	3.6 gal	2,650	2.5	UL/ETL
5585315	E0.8B8F1	1.6 gal	1,900	1.5	UL/ETL
5585320	E3.7K3H2	8.5 gal	2,400	2.5	UL/ETL
5585325	F3.2G3H1	4.2 gal	2,650	2.5	UL/ETL
5585435	E1.2B3F1	1.6 gal	2,500	1.5	CE

