



ZINKO

Ram Toe Cylinders

Model: RHC Series
Capacity: 5 ~ 25 Ton

Usage:

Widely used for bridge or plant construction, emergency lift for rescuer after earthquake or building corruption, and moving or installation of industrial machinery and shipyard equipment.

Special Features:

1. These toe cylinders are designed to lift loads with a very low clearance. The toe area can pick up the load from as low as 0.88 inches, which is the lowest pick up point in the industry.
2. Easily connecting the port to any hand pump or air pump. These toe cylinders will give the operator full control of the lift from a distance whenever close quarters operation is not accessible. Coupler connection port can be operated at any direction.
3. 5 and 10 ton models come with steel cylinder.
4. 10 and 25 ton models come with aluminum cylinder lighter weight for mobility.



RHC-15A



RHC-5



RHC-10



Model Number	Capacity (Ton)	Oil Capacity (in³)	Min. Height (in)		Max. Height (in)		Ram Lift (in)	Toe Area (in)	Base Area (in)	Weight (lbs)
			Toe	Head	Toe	Head				
RHC-5	5	11.2	0.87	11.75	5.79	16.67	4.92	2.25 x 2.88	7.12 x 7.12	45
RHC-10	10	25.8	1.18	14.33	6.10	19.25	4.92	2.34 x 3.70	9.75 x 7.88	100
RHC-15A	15	32.55	1.18	14.33	6.10	19.25	4.92	2.34 x 3.70	10.92 x 9.36	64
RHC-25A	25	65.14	1.34	15.67	7.25	21.58	5.91	2.48 x 4.88	11.70 x 12.20	180