

# SUNFIRE®



## RADIANT

DUAL FUEL  
DIESEL / #2 KEROSENE



# THE ULTIMATE ODORLESS HEATERS



**SF160**  
160,000 BTU

**SF80**  
80,000 BTU

**SF120**  
120,000 BTU

**NO SMELL**  **NO FUMES**



## SPECIFICATIONS

	SF80	SF120	SF160
BTU/Hour:	80,000	120,000	160,000
Heating Capacity:	1,900 Sq. Ft.	2,800 Sq. Ft.	3,700 Sq. Ft.
Fuel Types:	Diesel, Kerosene, #2 Fuel Oil	Diesel, Kerosene, #2 Fuel Oil	Diesel, Kerosene, #2 Fuel Oil
Fuel Tank Capacity:	6 Gallons	14 Gallons	18 Gallons
Flow Rate:	Diesel: .58 GPH Kerosene: .56 GPH	Diesel: .85 GPH Kerosene: .78 GPH	Diesel: 1.14 GPH Kerosene: 1.05 GPH
Run Time (Approx.):	Up to 10 Hrs.	Up to 16 Hrs.	Up to 16 Hrs.
Dimensions:	19.75" W x 26" L x 27.75" H	28.5" W x 32" L x 33.75" H	31" W x 35.5" L x 43" H
Dry Weight:	85 lbs.	125 lbs.	160 lbs.
Wet Weight (Full Tank):	127 lbs.	220 lbs.	305 lbs.
Electrical:	120V 1.1A 60HZ Compatible with 12V 800W+ Pure Sine Power Inverter	120V 1.8A 60HZ Compatible with 12V 800W+ Pure Sine Power Inverter	120V 1.6A 60HZ Compatible with 12V 800W+ Pure Sine Power Inverter

## RAPID ACCESS™ EASY MAINTENANCE HATCH

Hatch inside the burner assembly makes tuneups and nozzle changes quick and easy so you can spend less time on maintenance.

## THERMOSTAT OPTION



All models can be regulated with any standard or battery-operated wall thermostat.

Thermostat not included with SF80 and SF120. Thermostat included with SF160.

## KEY FEATURES

- Low Noise
- Safe & Odorless
- High Portability
- Rubber Flat-Free Wheels
- Heavy-Duty Construction
- Dual Fuel: Diesel & Kerosene
- Dust-Free Heating Experience
- Warms Objects & People Directly
- Safety: Flame Sensor & Tip Switch
- Made in the USA



## CALIFORNIA PROP 65

This product can expose you to ceramic fibers, which is known to the State of California to cause cancer. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

- Not for indoor household residential use.
- Proper ventilation required.

